

QUALIFIED BY IAE UNDER LICENSING AGREEMENT

V2500

ENGINE TRANSPORTATION STAND

D71STA00004G04



- > IAE V2500 POWERPLANT FOR AIRCRAFT A320 FAMILY
- > STANDARD AIRCRAFT TRANSPORTATION
- > STANDARD TRUCK TRANSPORTATION
- > UNDER WING ENGINE INSTALLATION

- > STOCK AVAILABILITY ON COMPONENTS
- > FREE ANNUAL FIT CHECK AND FUNCTION > REPAIR / RE CERTIFICATION
- > UPGRADES AND MODIFICATIONS



AOG - 24/7 HOTLINE: +1(802)4733341














DEDIENNE-AERO.COM | LEAPTOOLING.COM | NACELLETOOLING.COM



DEDIENNE
AEROSPACE

A stylized graphic of an airplane in flight, with a white outline and a blue shadow, positioned below the company name.

V2500 ENGINE STAND SPECIFICATIONS

	WEIGHT	2,100 Kg [4,624 lb]
	DIMENSIONS	4,419 mm X 2,413 mm X 1,549 mm [174in X 95in X 61in]
	USAGE	Transport, Install and Remove V2500 Engine
	USED WITH	-
	INTERFACES WITH	FAN FRAME TURBINE REAR FRAME
	BOOTSTRAP POINTS	On Engine Stand Cradle
	COUNTERWEIGHT	YES - To Balance Weight during Bootstrap Operation
	LIFTING SYSTEM	NO
	VERTICAL POSITIONS	1
	CASTER WHEEL TYPE	Swiveling Caster; Double Wheel with 2 Wheel Pins
	CASTER WHEEL POSITIONS	4 Positions
	CASTER WHEEL POSITIONS	1) Ground Position 2) Engine Position 3) Middle Course [To Change Lift Bar Orientation] 4) Empty Stand Caster Position
	ISOLATION	8 Shock Absorbing Mounts between Cradle and Trolley
	ISOLATION OBJECTIVE	Protect Engine Interfaces from shock, vibration and acceleration during transportation
	STACKABLE	YES - (Quantity =3)
	TOWING CAPABILITY	FORWARD AND AFT

