QUALIFIED BY IAE UNDER LICENSING AGREEMENT

V2500 ENGINE TRANSPORTATION STAND

P/N: D71STA00004G04

- IAE V2500 ENGINE FOR A320 FAMILY
- STANDARD AIRCRAFT TRANSPORTATION
- STANDARD TRUCK TRANSPORTATION
- ON-WING ENGINE INSTALLATION
- STACKABLE
- STOCK AVAILABILITY ON COMPONENTS
- REPAIR / RECERTIFICATION
- UPGRADES AND MODIFICATIONS





OFFICIAL

-



AOG - 24/7 HOTLINE: +1(802)4733341 DEDIENNE-AERO.COM | LEAPTOOLING.COM | NACELLETOOLING.COM In O

V2500 ENGINE STAND SPECIFICATIONS

\triangle	WEIGHT	2300 kg [5,070 lbs]
\longleftrightarrow	DIMENSIONS	4419 x 2413 x 1549 mm [174 x 95 x 61 in]
ŝ	USAGE	Transport, remove and install V2500 engine
C	INTERFACES WITH	Fan Frame Turbine Rear Frame
) , , , , , , , , , , , , ,	BOOTSTRAP POINTS	On engine stand cradle
00	COUNTERWEIGHT	Yes - To balance weight during bootstrap operation
$\uparrow \downarrow$	LIFTING SYSTEM	No
	VERTICAL POSITIONS	1
Q	CASTER WHEEL TYPE CASTER WHEEL POSITIONS	 Swiveling caster; double wheel with 2 wheel pins 1) Ground position 2) Engine position 3) Middle course (To change lift bar orientation) 4) Empty stand caster position
5≤	ISOLATION	8 shock absorbing mounts between cradle and trolley
	ISOLATION OBJECTIVE	Protect engine Interfaces from shock, vibration and acceleration during transportation
\bigotimes	STACKABLE	Yes (Quantity: 3)
$\stackrel{\frown}{\leftrightarrow}$	TOWING CAPABILITY	Forward and Aft



HIGH DEMAND SPARE PARTS	SERVICES	P/N
CASTER ASSEMBLY	PERIODIC RECERTIFICATION	PDEPANN2200040
STEERING BEAM	SHOCK ABSORBER REPLACEMENT	PDEPREP2200128
TOWBAR		
WRENCH	—	
SHOCK ABSORBERS*		
Check with the manufacturer the periodicity of your shock absorber replacement	—	



06-2022 // 3

AOG - 24/7 HOTLINE: +1(802)4733341